



# DECLARATION OF PERFORMANCE

in accordance with Appendix III to Regulation (EU) No. 305/2011  
**No. 03 0002**

Type of product  
**Plaster with organic binding agents**

Identification mark  
**KEIM Indusil**  
 (alle Varianten)  
 Batch number: see packaging of product

Intended use  
**Plaster with organic binding agents for use as exterior or interiorcoating  
 for walls, ceilings, pillars and divider walls**

Manufacturer  
**Keimfarben GmbH, Keimstraße 16, D-86420 Diedorf**

System for evaluation and verification of constancy of performance  
**System 3**

The notified body  
**HFM TU München, Identification number 797**  
 has performed the type approval test of the product respective to fire behavior accordant to System 3 and  
 issued the following:  
**Classification report No. B9421**

## Declared performance

Essential characteristics	Performance	Harmonized technical specification
Water vapor permeability	V1	EN 15824:2009
Water absorption	W3	EN 15824:2009
Adhesionstrength	≥ 0.3 MPa	EN 15824:2009
Durability (Frost resistance)	Permeability rate in accordance to EN 1062-3 is ≤ 0.5 kg/(m <sup>2</sup> h <sup>0.5</sup> )	EN 15824:2009
Thermal conductivity	NPD	EN 15824:2009
Fire behavior	A2-s1,d0 (when applied to mineral subsurfaces)	EN 15824:2009
Hazardous substances	NPD	EN 15824:2009



The performance of the product for which this declaration of performance was issued conforms to the declared performance. The manufacturer stated in this declaration of performance bears sole responsibility for the preparation of this declaration of performance.

Signed for the manufacturer and on behalf of the manufacturer by:

Peter Jaser, Manager of quality assurance and color metrics

Diedorf, 01.07.2013

  
p. p. Peter Jaser

Appendix:  
Material safety data sheet