



M60 PAINTING/CLEAR FINISHING

110 INTERIOR PAINT - UNPAINTED & PREVIOUSLY PAINTED:

KEIM INNOSTAR SYSTEM

A silicate based high quality, one coat, non-combustible paint for interior walls and ceilings. It provides long-term decoration and is available in white.

Manufacturer: Keim Mineral Paints Limited, Santok Building, Deer Park Way, Telford, Shropshire TF2 7NA
Tel: 01952 231250 Fax: 01952 231251 email sales@keimpaints.co.uk

Reference: Keim Innostar

Preparation:

Any loose, flaking and unstable material must be identified and then thoroughly removed using stiff brushes and broad bladed scrapers to get back to a sound edge; these edges should then be feathered in. Ensure that any paint materials left remaining and the underlying substrate is sound and adhering well. Any gloss or shiny surfaces should be thoroughly flatted down using sand or emery paper to create a good key.

Keim Dolomitspachtel

Any cracks or where there is a need to equalise the surface should be filled using Keim Dolomitspachtel, a ready to use silicate mineral filler, brush or trowel applied to a pre-wetted surface and dressed back to the required level. On new surfaces we would suggest that a period of at least 15 days is allowed, prior to the application of Keim Paints.

When all surfaces are clean, sound, wind dry, dust free and free from all surface contaminants, decoration using Keim Mineral Paints may proceed.

Keim Granital Dilution

If necessary, highly absorbent or friable surfaces should be treated with Keim Granital Dilution, a liquid silicate binder, brush applied and left for a minimum period of 12 hours.

Application:

Keim Innostar

Apply a single coat of Keim Innostar, a mineral matt finish silicate based paint system. Keim Innostar may be applied by brush, roller or air-less spray (0.79mm).